

3M™ Overhead Projector Model 1610

Budget

For Small Meeting Rooms

The 3M™ Model 1610 is the perfect, economical, energy efficient and lightweight projector designed for small meeting spaces and small budgets. The 3M 1610 gives you clear sharp images, a multi-range fixed focus which allows you to move the overhead up to three feet without refocusing, and a whisper-quiet fan that won't distract your audience from the presentation. The 3M 1610 offers convenient built-in carry grips for easy transport — no more broken straps or handles. UL/cUL approved.



KEY FEATURES

- > Ultra quiet fan (37dB typical) doesn't distract from your presentation
- > Uses approximately 50% less energy when compared to a standard 360 watt EYB lamp projector
- > Open lens designed for easy cleaning
- > Polymer arm assembly is tough, yet lightweight
- > Easy on/off switch right at your fingertips
- > Multi-range fixed focus stays focused between use
- > 1000 ANSI lumens enhance your visuals and give you clear sharp images in small meeting spaces
- > Cool stage keeps transparency film from curling
- > Wide-angle lens delivers beautiful images, even when the projector is close to the screen
- > Compact for easy transport
- > Two-year warranty

ORDER NUMBER: HK-4000-0036-8

UPC Code: 0-51125-59544-5

OPTIONAL ACCESSORIES: Replacement lamp, dust cover, and projection screens.

TECHNICAL SPECIFICATIONS

OPTICAL PERFORMANCE

- > Head: Open singlet (*one element*)
- > Illumination: 1000 ANSI lumens typical
- > Stage aperture: 254 mm x 254 mm (*10" x 10"*)
- > Stage temperature: 40°C
- > Focal Length: 295mm (*11.6"*)

LAMP DESCRIPTION

- > Lamp changer: No
- > Lamp Type: FCS (*24 volts, 150 watts*) (1 Lamp included)
- > Lamp Life: 50 hours average

PHYSICAL CHARACTERISTICS

- > Width: 317.50 mm (*12.5"*)
- > Depth: 330.20 mm (*13"*)
- > Height (body): 254 mm (*10"*)
- > Weight: 11 lbs. (*5 kg*)

ELECTRICAL FEATURES

- > Power-cord length: 3.05 m. (*10'*)
- > Voltage rating: 120VAC, 60Hz
- > Agency approval: UL/cUL

MECHANICAL

- > Thermal protection circuit: cuts power to the lamp if the projector exceeds safe operating temperature.



www.3M.com/meetings

Specifications subject to change without notice.

3M is a trademark of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

3M Visual Systems

Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000
1-800-328-1371
www.3m.com/meetings

3M Mexico, S.A. de C.V.

Apartado Postal 14-139
Mexico, D.F. 07070
Mexico



Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of two years from the time of purchase. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M Innovation