



Revolabs Solo Single Channel Wireless Microphone Product Specifications

Order#02-DSKSYS-LN-NM
Solo Wireless Microphone ordered separately

Charger Base

- 3.9" x 2.4" x 1.0"
- 10 cm x 6 cm x 2.56 cm

Radio Frequency

- 1.92-1.93 GHz (DECT in UPCS)

Connector

- Power-5V DC, proprietary 0.7 mm
- Mini USB-5 pin connector
- Audio unbalanced In/Out 2.5mm
- Tip: Audio Out
- Ring: Audio In
- Shield: GNC

Power Adapter

- 110V AC, 60Hz to 5V DC, 300mA

Range

- 65' (20 m) approximately
- Out-of-range alarm

Battery

- Lithium Polymer
- Up to 8 hours talk time

Audio Bandwidth

- 100-6800 Hz

Encryption

- 128-bit

Environmental Requirements

- 40-100 degrees F (5-40 C)
- 20-85% Humidity

Includes:

- 6' (1.82 m) power cord
- 5' (1.5 m) USB cable

Wireless
Flexible
Secure
Rechargeable
Cost-effective
Easy-to-use

Applications:
Tele-conferencing
Video-conferencing
Distance learning
Speech recognition



Québec Montréal
Tél. : (418) 681-2470 Tél. : (514) 871-1994

www.presence.qc.ca

Hear Every Word!